UT352
Sound Level Meter

UT352 sound level meter can measure noise level and output results in dB. A or C weighted modes can be selected depending on the application. UT352 consume very little power and can continuously work up to 20 hours. They are suitable for industrial and environmental sound level measurements.



UT352

Specifications	Range	UT352
Certificates	**CE, UKCA**	
Range	30~130dB	
Accuracy	±1.5dB	
Frequency	31.5Hz~8000Hz	
Frequency weighting	A&C	
Sampling rate (Fast)	8 times/s	
Sampling rate (Slow)	1 time/s	
Data storage	63	
Analog outputs (AC)	0.707Vrms full scale; Output impedance: around 600Ω	
Analog outputs (DC)	2Vrms full scale; 10mV/dB; Output impedance: around 100Ω	

Features
Powered by batteries or external power source
Data hold
LCD backlight
A (ear)/C (machine) weighted modes
Auto power off (cancelable)
63 sets of data storage
AC/DC analog signal output
Simulated analog bar
Manual/auto range selectable
Analog bar graph: 30~130dB
Low battery indication: ≤4.8V
MAX/MIN
High/low alarm

Characteristics	
Standard accessories	Windscreen, leather box, English manual
Power	1.5V battery (LR6) x 4
Display	53 x 41mm
Product size	273 x 70 x 39mm
Product net weight	330g
Standard individual packing	Gift Box
Standard quantity per carton	10pcs
Standard carton measurement	670 x 415 x 120mm
Standard carton gross weight	7.3kg